



Record UK Ltd

n55Plus

## Cleancord

By Record UK Ltd

### Detailed description

The record Cleancord stainless steel sliding door is designed for use in clean rooms to automatically separate clean zones. Its smooth, flush-finished surface prevents dirt from collecting, and the proven record system is reliable, low-noise and user-friendly.

#### Features:

- Available with radiation protection.
- Flush glazing in line with customer requirements.
- Handles on both sides (stainless V2A).
- Recessed handles (to allow panels to slide parallel).
- If required, door panels can also be finished in plastic of any colour.

#### Benefits:

- Convenient door automation.
- Hygienic.
- Easy-to-clean surfaces.

#### Applications:

For rooms with hygienic requirements and other areas such as operating theatres in hospitals and clinics, research and laboratory rooms, pharmaceutical production facilities, quarantine zones and clean rooms for the production of foodstuffs.

### Product guidance - As Standard

#### Door frame:

- Thickness: 40 mm, deviating for special designs.
- Profile: Anodized aluminium, reinforced if necessary.

#### Opening width:

Up to 6000 mm (wider on request).

#### Clear height of passage:

Up to 4500 mm (higher on request).

#### Door leaf weight (maximum):

1 x 220 kg/ 2 x 110 kg (higher weights on request).

#### Mains voltage:

230 V AC, 50/ 60 Hz.

#### Rated power:

240 W.

Consumption in idle mode:

25 W.

Temperature range:

0–60°C.

Humidity range:

10–93% relative humidity, non-wetting.

## Product specification

### Manufacturer

- Name: Record UK Ltd  
- Web: [www.recorduk.co.uk](http://www.recorduk.co.uk)  
- Email: [info@recorduk.co.uk](mailto:info@recorduk.co.uk)  
- Tel: +44 (0)1698 376411  
- Fax: +44 (0)1698 376422  
- Address: 9 Watt Place,Hamilton International,Business Park,Glasgow G72 0AH

Product reference K1-A - Single door.  
K2-A - Double door.

Size [\_\_\_\_\_]

Core Solid particleboard  
Tubular particleboard

Finish HPL laminate  
Galvanized sheet steel  
Stainless steel, powder coated

Colour [\_\_\_\_\_]

Lead inserts Not required  
Required

